

## Deep groove ball bearings with extended inner ring US, USC and UD type

Dimensions								Basic radial load		Designation	Weight
d	d	D	B	C <sub>1</sub>	n	r <sub>s</sub>	M	dyn.	stat.	bearing	
mm	inch	mm	mm	mm	mm	mm	mm	C <sub>r</sub>	C <sub>0r</sub>	-	Kg
19.05	3/4"	47	25	14	7	1	M5x0.8	12.8	6.65	<b>US204-12</b>	0.132
		47	25	14	7	1	M5x0.9	12.8	6.65	<b>USC204-12</b>	0.134
20		47	14			1		12.8	6.65	<b>UD204</b>	0.104
		47	25	14	7	1	M5x0.8	12.8	6.65	<b>US204</b>	0.138
		47	25	14	7	1	M5x0.9	12.8	6.65	<b>USC204</b>	0.14
22.225	7/8"	52	27.5	15	7.5	1	M6x1	14	7.85	<b>US205-14</b>	0.15
		52	27.5	15	7.5	1	M6x1	14	7.85	<b>USC205-14</b>	0.153
25		52	15			1		14	7.85	<b>UD205</b>	0.128
		52	27.5	15	7.5	1	M6x1	14	7.85	<b>US205</b>	0.147
		52	27.5	15	7.5	1	M6x1	14	7.85	<b>USC205</b>	0.15
25.4	1"	52	15			1		14	7.85	<b>UD205-16</b>	0.13
		52	27.5	15	7.5	1	M6x1	14	7.85	<b>US205-16</b>	0.144
		52	27.5	15	7.5	1	M6x1	14	7.85	<b>USC205-16</b>	0.147
28.575	1"1/18	62	28.5	16	8	1	M6x1	19.5	11.3	<b>US206-18</b>	0.266
		62	28.5	16	8	1	M6x1	19.5	11.3	<b>USC206-18</b>	0.269
30		62	28.5	16	8	1	M6x1	19.5	11.3	<b>US206-18</b>	0.252
		62	28.5	16	8	1	M6x1	19.5	11.3	<b>USC206-18</b>	0.255
30.163	1"3/16	62	28.5	16	8	1	M6x1	19.5	11.3	<b>US206-19</b>	0.25
		62	28.5	16	8	1	M6x1	19.5	11.3	<b>USC206-19</b>	0.253
35		72	17			1.1		25.7	15.4	<b>UD207</b>	0.277
		72	34	17	8.5	1.1	M8x1	25.7	15.4	<b>US207</b>	0.42
		72	34	17	8.5	1.1	M8x1	25.7	15.4	<b>USC207</b>	0.42
45		85	21			1.1		32.7	20.4	<b>UD209F2</b>	0.457