

Rulmenți radial-axiali cu role conice pe un rând, cu guler la inelul exterior

Dimensiuni					Simbol		Serie		Sarcina radiala de baza. Factori				Turatia limita		Masa	Dimensiuni de montaj							
d	D	B	C	T	$r_{1s,2s}$	$r_{3s,4s}$	D_1	b	a	rulment	ISO	din.	e	Y	stat.	Y_0	unsoare	ulei	Masa	d_{u1}	d_u	D_u	r_u
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	-	Kg	KN	-	KN			min^{-1}	min^{-1}	Kg	mm	mm	mm	mm
20	47	14	12	6.25	1	1	51	3	11	30204 AR	2DB	26	0.4	1.7	29	0.9	8000	11000	0.13	27	26	43	1
25	52	15	13	6.25	1	1	57	3.5	12	30205 AR	3CC	29.5	0.4	1.6	36	0.9	7500	10000	0.16	31	31	48	1
30	62	16	14	6.75	1	1	67	3.5	14	30206 AR	3DB	38	0.4	1.6	48	0.9	6300	8500	0.23	37	36	57	1
	62	20	17	8.25	1	1	67	4	15	32206 AR	3DC	47.5	0.4	1.6	65	0.9	6300	8500	0.29	37	36	59	1
	72	19	16	8.75	1.5	1.5	77	4	15	30306 AR	2FB	53	0.3	1.9	65	1.1	5600	7500	0.4	39	37	66	1.5
	72	27	23	11.8	1.5	1.5	77	6	18	32306 AR	2FD	72.3	0.3	1.9	97	1.1	5600	7000	0.58	40	37	66	1.5
35	72	17	15	7.25	1.5	1.5	77	4	15	30207 AR	3DB	49.4	0.4	1.6	58	0.9	5300	7000	0.34	44	42	67	1.5
	72	23	19	10.3	1.5	1.5	77	4.5	17	32207 AR	3DC	61.6	0.4	1.6	80	0.9	5300	7000	0.42	43	42	67	1.5
	80	21	18	8.25	2	1.5	85	4.5	16	30307 AR	2FB	68.2	0.3	1.9	83	1.1	5000	6700	0.54	45	44	74	2
	80	31	25	13.8	2	1.5	85	6	20	32307 AR	2FE	88.2	0.3	1.9	120	1.1	4800	6300	0.76	44	44	74	2
40	80	18	16	7.75	1.5	1.5	85	4	16	30208 AR	3DB	58.5	0.4	1.6	70	0.9	4800	6300	0.44	49	47	74	1.5
	80	23	19	10.3	1.5	1.5	85	4.5	19	32208 AR	3DC	71	0.4	1.6	95	0.9	4800	6300	0.53	48	47	75	1.5
	90	23	20	9.75	2	1.5	95	4.5	19	30308 AR	2FB	81	0.4	1.7	105	0.9	4500	6000	0.73	52	49	82	2
	90	33	27	14.3	2	1.5	95	6	23	32308 AR	2FD	110	0.4	1.7	156	0.9	4000	5300	1.03	50	49	82	2
45	85	19	16	8.75	1.5	1.5	90	4	18	30209 AR	3DB	63	0.4	1.5	83	0.8	4500	6000	0.49	54	52	80	1.5
	85	23	19	10.3	1.5	1.5	90	4.5	20	32209 AR	3DC	75	0.4	1.5	103	0.8	4500	6000	0.58	53	52	80	1.5
	100	25	22	10.3	2	1.5	106	5	21	30309 AR	2FB	101	0.4	1.7	130	0.9	4000	5300	0.96	59	54	92	2
	100	36	30	15.3	2	1.5	106	7	25	32309 AR	2FD	132	0.4	1.7	188	0.9	3600	4800	1.3	56	54	93	2
50	90	20	17	8.75	1.5	1.5	95	4	19	30210 AR	3DB	70.5	0.4	1.4	95	0.8	4300	5600	0.55	58	57	85	1.5
	90	23	19	10.3	1.5	1.5	95	4.5	21	32210 AR	3DC	76.5	0.4	1.4	106	0.8	4300	5600	0.63	58	57	85	1.5
	110	27	23	11.3	2.5	2	116	5	23	30310 AR	2FB	120	0.4	1.7	156	0.9	3600	4800	1.23	65	60	102	2.5
	110	40	33	17.3	2.5	2	116	8	27	32310 AR	2FD	165	0.4	1.7	239	0.9	3200	4300	1.89	62	60	102	2.5
55	100	21	18	9.25	2	1.5	106	4.5	20	30211 AR	3DB	84.5	0.4	1.5	112	0.8	3800	5000	0.72	64	64	94	1.5
	100	25	21	10.8	2	1.5	106	5	22	32211 AR	3DC	99	0.4	1.5	138	0.8	3800	5000	0.86	63	64	95	1.5
	120	43	35	18.5	2.5	2	127	8	29	32311 AR	2FD	187	0.4	1.7	276	0.9	3000	4000	2.29	68	65	111	2
60	110	22	19	9.25	2	1.5	116	4.5	22	30212 AR	2EB	91.5	0.4	1.5	122	0.8	3400	4500	0.9	70	69	103	2
	110	28	24	10.8	2	1.5	116	5	24	32212 AR	2EC	120	0.4	1.5	170	0.8	3400	4500	1.14	69	69	104	2
	130	46	37	19.5	3	2.5	137	8	31	32312 AR	2FD	216	0.4	1.7	318	0.9	2600	3600	1.92	74	72	120	3
65	120	23	20	9.25	2	1.5	127	4.5	23	30213 AR	3EB	110	0.4	1.5	147	0.8	3000	4000	1.14	77	74	113	2
	120	31	27	11.8	2	1.5	127	6	27	32213 AR	3EC	142	0.4	1.5	206	0.8	3000	4000	1.54	76	74	115	2
70	125	24	21	10.3	2	1.5	132	5	25	30214 AR	3EB	120	0.4	1.4	163	0.8	3000	4000	1.27	81	79	118	2
	125	31	27	12.3	2	1.5	132	6	28	32214 AR	3EC	150	0.4	1.4	220	0.8	2800	3800	1.62	80	79	119	2

