

Cylindrical roller bearings, four row

Dimensions						Basic radial load		Speed limit		Designation	Weight
d	D	B	r _s min.	r _{1s} min.	F	dyn. C _r	stat. C _{0r}	grease	oil		
mm	mm	mm	mm	mm	mm	KN	KN	min ⁻¹	min ⁻¹	-	Kg
200	310	200	2.1	2.1	229	1920	4227	1700	2200	NNU6040EM	59
220	340	218	3	3	250	2234	4845	1600	2000	NNU6044EM	76
240	360	218	3	3	272	2355	5518	1400	1800	NNU6048EMC3NA	82
	360	218	3	1	272	2355	5518	1400	1800	NNU6048EMC3NAW8	82
	360	218	3	1	272	2355	5518	1400	1800	NNU6048EMC4NAW8	82
260	400	250	4	4	296	2832	6564	1300	1700	NNU6052EM	120
280	420	250	4	4	314	3005	7016	1200	1600	NNU6056EMC3NA	128
	420	250	4	1.5	314	3005	7016	1200	1600	NNU6056EMC3NAW8	128
	420	250	4	1.5	314	3005	7016	1200	1600	NNU6056EMC4NAW8	128
300	460	290	4	4	341	3879	9319	1100	1500	NNU6060EMC3NA	186
	460	290	4	1.5	341	3879	9319	1100	1500	NNU6060EMC3NAW8	186
	460	290	4	1.5	314	3879	9319	1100	1500	NNU6060EMC4NAW8	186
320	480	290	4	4	361	3970	9767	950	1300	NNU6064EMC3NA	193
	480	290	4	1.5	361	3970	9767	950	1300	NNU6064EMC3NAW8	193
	480	290	4	1.5	361	3970	9767	950	1300	NNU6064EMC4NAW8	193
340	520	325	5	5	385	4980	11720	900	1200	NNU6068EM	263
	520	325	5	5	385	4980	11720	900	1200	NNU6068EMC3NAW8	263
360	540	325	5	5	405	4292	11665	900	1200	NNU6072EM	274
400	600	355	5	5	450	5282	15295	900	1200	NNU6080EM	375