

Cylindrical roller and cage radial assemblies

Dimensions			Basic radial load		Speed limit		Designation	Weight
F	E	B	dyn. C_r	stat. C_{0r}	grease	oil		
mm	mm	mm	KN	KN	min ⁻¹	min ⁻¹	-	Kg
70	85	40	105	175	6000	7000	Wa1070	0.39
	106	41.3	186	210	5300	6300	K70x106x41AM	1.14
72	100	27.3	126	148	5300	6300	K72x100x27AM	0.568
120	140	65	245	502	3500	4300	Wa12x140x65	1.24
121.5	173.5	49.5	407	520	3200	3800	K121x173x49AM	4.4
130	158	70	360	671	3200	3800	Wa2526	2.95
150	178	70	390	773	2800	3400	Wa2630	2.5
180	220	70	565	1038	2400	2800	Wa180x220x70	5.1
224.8	248.8	30	116	207	2000	2400	K224x248x30A	1.94
280.5	300.5	48	315	918	1600	1900	Wa2756	2.4
358	386.1	29	270	651	1200	1500	Wa2771	2.6
460	500	120	1630	5546	900	1100	Wa460x500x120	18.9
550	590	120	1765	6514	800	950	Wa550x590x120	22
650	690	69.7	1090	3713	670	800	Wa27/650	14.5