

Dimensions				Designation				Basic radial load. Factors							Speed limit		Weight	
d ₁	d	D	B	r _s min.	d ₂	B ₁	B ₂	Bearing	Sleeve	dyn. C _r	e	Y ₁	Y ₂	stat. C _{0r}	Y ₀	grease	oil	Kg
mm	mm	mm	mm	mm	mm	mm	mm	-	-	KN	KN	KN	KN	KN	KN	min ⁻¹	min ⁻¹	Kg
400	400	650	200	6	520	272	62	23180CAKW33	H3180H	4100	0.28	2.4	3.6	7730	2.5	530	700	335.600
	400	650	200	6	520	272	62	23180MBKW33	H3180H	3920	0.28	2.4	3.6	7164	2.5	480	630	340.600
	400	720	256	6	520	328	62	23280CAKF3W33	H3280H	5950	0.35	1.9	2.9	10807	1.8	380	500	546.000
400	420	620	150	5	490	212	52	23084CAKW33	H3084H	3050	0.24	2.8	4.2	6055	2.7	560	750	198.700
	420	620	150	5	490	212	52	23084MBKW33	H3084H	2825	0.24	2.8	4.2	5480	2.7	500	670	203.700
	420	700	224	6	540	304	70	23184CAKW33	H3184H	4600	0.33	2	3	9000	2	500	670	447.200
	420	760	272	7.5	540	352	70	23284CAKW33	H3284H	6575	0.35	1.9	2.9	11714	1.8	360	480	652.000
	420	760	272	7.5	540	352	70	23284MBKW33	H3284H	6215	0.35	1.9	2.9	10720	1.8	320	430	665.000
410	440	650	157	6	520	228	60	23088CAKW33	H3088H	3345	0.22	3	4.6	6700	2.8	530	700	245.200
	440	720	226	6	560	307	70	23188CAKW33	H3188H	5250	0.3	2.3	3.4	10000	2.2	500	670	464.000
	440	790	280	7.5	560	361	70	23288CAKW33	H3288H	6700	0.35	1.9	2.9	12780	1.8	360	480	730.000
430	460	680	163	6	540	234	60	23092CAKW33	H3092H	3300	0.18	3.7	5.6	6900	3.7	500	670	274.500
	460	680	163	6	540	234	60	23092MBKW33	H3092H	3200	0.18	3.7	5.6	6170	3.7	450	600	278.500
	460	760	240	7.5	580	326	75	23192CAKW33	H3192H	5760	0.3	2.3	3.4	11025	2.2	480	630	557.000
	460	830	296	7.5	580	382	75	23292CAKW33	H3292H	7350	0.35	1.9	2.9	14350	1.9	340	450	849.000
450	480	700	165	6	560	237	60	23096CAKW33	H3096H	3300	0.23	2.9	4.4	6900	2.9	480	630	288.300
	480	790	248	7.5	620	335	75	23196CAKW33	H3196H	5800	0.3	2.3	3.4	11800	2.2	450	600	618.000
470	500	670	128	5	580	201	68	239/500CAKW33	H39/500H	2530	0.17	4	6	5800	4	480	630	206.000
	500	720	167	6	580	247	68	230/500MBKW33	H30/500H	3740	0.21	3.2	4.8	7815	3.2	430	560	306.800
	500	830	264	7.5	630	356	80	231/500CAKW33	H31/500H	6550	0.3	2.3	3.4	13200	3.2	430	560	723.000
500	530	710	136	5	630	216	68	239/530CAKW33	H39/530H	2980	0.17	4	5.9	6755	4	450	600	241.000
	530	780	185	6	630	265	68	230/530CAKW33	H30/530H	4985	0.23	2.9	4.4	10542	2.9	450	600	420.000
530	560	750	140	5	650	227	75	239/560CAKW33	H39/560H	2980	0.16	4.2	6.3	7451	4	450	600	276.000
	560	820	195	6	650	282	75	230/560CAKW33	H30/560H	5245	0.22	3	4.6	11134	2.8	430	560	472.000
560	600	800	150	5	700	239	75	239/600CAKW33	H39/600H	3640	0.16	4.2	6.3	8420	4	400	530	348.000
	600	870	200	6	700	289	75	230/600MBKW33	H30/600H	5610	0.22	3	4.6	12020	2.8	360	480	556.000
600	630	850	165	6	730	254	75	239/630CAKW33	H39/630H	4290	0.17	4	5.9	9910	4	380	500	401.000
	630	920	212	7.5	730	301	75	230/630CAKW33	H30/630H	6175	0.21	3.2	4.8	13173	3.2	380	500	624.000
630	670	900	170	6	780	264	80	239/670CAKW33	H39/670H	4370	0.17	4	5.9	10300	4	360	480	489.000
	670	980	230	7.5	780	324	80	230/670CAKW33	H30/670H	6580	0.21	3.2	4.8	14400	3.2	340	450	793.000
670	710	950	180	6	830	286	90	239/710CAKW33	H39/710H	4680	0.17	4	5.9	12230	4	340	450	582.000
	710	1030	236	7.5	830	342	90	230/710CAKW33	H30/710H	6665	0.21	3.2	4.8	17000	3.2	320	430	891.000
710	750	1000	185	6	870	291	90	239/750CAKW33	H39/750H	5474	0.16	4.2	6.3	13085	4	320	430	646.000
750	800	1060	195	6	920	303	90	239/800MBKW33	H39/800H	6131	0.16	4.2	6.3	15016	4	280	360	772.000
	800	1150	258	7.5	920	336	90	230/800MBKW33	H30/800H	9389	0.2	3.4	5	21295	3.2	260	340	1206.000
800	850	1120	200	6	980	308	90	239/850CAKW33	H39/850H	6450	0.16	4.2	6.3	15880	4	280	380	867.000
850	900	1180	206	6	1030	326	100	239/900CAKW33	H39/900H	6930	0.15	4.5	6.7	17120	4.5	280	360	979.000
900	950	1250	224	7.5	1080	344	100	239/950CAKW33	H39/950H	7310	0.15	4.5	6.7	19500	4.5	260	340	1117.000